



SH PLATING

| SYMBOL | MIL |                    | MET  |                    |
|--------|-----|--------------------|------|--------------------|
|        | MIN | NOM                | MIN  | MAX                |
| A      | -   | -                  | -    | 1.75 <sub>8</sub>  |
| A1     | 0.1 | -                  | -    | 0.225              |
| A2     | 1.3 | 1.40               | -    | 1.50               |
| A3     | 0.6 | 0.65               | -    | 0.70               |
| b      | 0.3 | -                  | 0.41 | 0.47               |
| b1     | 0.3 | -                  | -    | 0.44               |
| c      | 0.2 | 0.20               | -    | 0.24               |
| c1     | 0.1 | 0.20               | -    | 0.21               |
| D      | 4.8 | 4.90               | -    | 5.00               |
| E      | 5.8 | 5.90               | -    | 6.20               |
| E1     | 3.8 | 3.90               | -    | 4.00               |
| e      | -   | 1.2 <sup>BSC</sup> | -    | 1.2 <sup>BSC</sup> |
| L      | 0.5 | 0.5                | -    | 0.80               |
| L1     | -   | 1.0 <sup>REF</sup> | -    | 1.0 <sup>REF</sup> |
| L2     | 0.3 | 0.40               | -    | 0.50               |
| 0      | 0   | -                  | -    | 8°                 |

|                |             |          |   |
|----------------|-------------|----------|---|
| Signature      |             | Date     | <br>Tianshui Huateng Technology Co., LTD. |
| Verified By    | LI Jianjun  | DWG No.  |   |
| Verified By    | WEI Cunjing | HTFS0060 | REV. A                                    |
| Approved By    | LI Daxiao   | Unit     | mm  |
| Title          |             |          | SOPL BOD (8R)                             |
| REF No.        |             |          | JEDEC MS-012                              |
| Effective Date |             |          | 2016/04/27                                |